

610-630w

Draco Module Series

N-TOPCON HIGH EFFICIENCY 132-16BB-W-WG

Bloomberg
NEW ENERGY FINANCE

Tier1



Product Characteristics

- Optimized cell size brings higher power and Lower transportation costs

Extraordinary Product Performance


- N-type with lower LID and LeTID
- Up to 30% additional power yield benefited from bifacial technology and over 80% cell bifaciality
- Competitive high-temperature performance with ameliorated temperature coefficient
- Better weak illumination response, higher power generation with N-TOPCon technology

High Quality Reliability

- Industry-leading cell processing technology and dual glass contributes to excellent anti-PID characteristic

Wider Application Conditions

- Universal solution for residential and C&I rooftops
- BIPV, vertical installation, snowfield, high-humid area, windy and dusty area
- Easy for integration, designed for compatibility with existing mainstream inverters and diverse mounting systems



MANAGEMENT SYSTEM CERTIFICATES

- IEC 61215, IEC 61730
- ISO 9001
2015 / Quality management system
- ISO 14001
2015 / Standards for environmental management system
- ISO 45001
2018 / International standards for occupational health & safety



Electrical Typical Values

Model	1000V		PS610L8GF-22/WNH		PS615L8GF-22/WNH		PS620L8GF-22/WNH		PS625L8GF-22/WNH		PS630L8GF-22/WNH	
	1500V		PS610L8GFH-22/WNH		PS615L8GFH-22/WNH		PS620L8GFH-22/WNH		PS625L8GFH-22/WNH		PS630L8GFH-22/WNH	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Rated Power (Pmpp)	610	467	615	471	620	475	625	479	630	482	630	482
Rated Current (Impp)	14.84	11.95	14.87	11.98	14.90	12.00	14.93	12.02	14.96	12.05	14.96	12.05
Rated Voltage (Vmpp)	41.11	39.08	41.36	39.32	41.62	39.56	41.87	39.80	42.12	40.04	42.12	40.04
Short Circuit Current (Isc)	15.48	12.47	15.52	12.50	15.56	12.53	15.60	12.56	15.64	12.60	15.64	12.60
Open Circuit Voltage (Voc)	48.95	46.87	49.22	47.13	49.50	47.40	49.77	47.65	50.04	47.91	50.04	47.91
Module Efficiency (%)	22.58		22.77		22.95		23.14		23.32			

STC (Standard Testing Conditions): Irradiance 1000W/m², AM 1.5, Cell Temperature 25°C

NOCT (Nominal Operation Cell Temperature): Irradiance 800W/m², Ambient Temperature 20°C, Spectra at AM1.5, Wind at 1m/s

BNPI

Maximum Power (Pmax)	672	677	683	688	694
Optimum Operating Current (Impp)	16.35	16.38	16.41	16.44	16.48
Optimum Operating Voltage (Vmpp)	41.11	41.36	41.62	41.87	42.12
Short Circuit Current (Isc)	17.05	17.08	17.14	17.17	17.22
Open Circuit Voltage (Voc)	48.95	49.22	49.50	49.77	50.04

BNPI: Front side irradiation 1000W/m², back side reflection irradiation 135W/m², AM 1.5, ambient temperature 25°C

Mechanical Characteristics

Cell Type	N Type Monocrystalline
Dimension (L × W × H)	Length: 2382mm (93.78 inch) Width: 1134mm (44.65 inch) Height: 30mm (1.18 inch)
Weight	32.6kg (71.87 lbs)
Glass	2.0mm/2.0mm Heat Strengthened Glass
Frame	Anodized Aluminium Alloy
Cable (Including Connector)	4mm ² (IEC), (+): 350mm, (-): 250mm or Customized Length
Junction Box	IP 68 Rated

Temperature Ratings

Voltage Temperature Coefficient	-0.25%/°C
Current Temperature Coefficient	+0.04%/°C
Power Temperature Coefficient	-0.29%/°C
Power Tolerance	0~+3%
NOCT	42±2°C
Bifaciality	80±5%




Absolute Maximum Rating

Operating Temperature	From -40 to + 85°C
Hail Diameter @ 80km/h	Up to 25mm
Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Maximum Series Fuse Rating	30A
PV Module Classification	II
Fire Rating (IEC61730)	C
Maximum System Voltage	DC 1000V/1500V

Packing Configuration

Container	40' HQ
Pieces/Container	720
Pcs/Pallet	36
Pallets/Container	20

Electrical Characteristics



Note:mm (inch)